



Product Specification

Domestic Range

C

200 L High Gain Solar

| Capacity | Type | Model | Installation |
|----------|----------|-----------------|----------------|
| 200L | Unvented | High Gain Solar | Floor Standing |

Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 83 W

Constructive Specifications

| | |
|---|---|
| Capacity | 200 L |
| Cylinder Material | Stainless Steel Duplex LDX 2101 |
| Thermal Insulation | Polyurethane foam CFC-Free and HCFC Free |
| Casing | Painted Galvanised Carbon Steel DX51D |
| Coil Material | Stainless Steel Tube AISI 316L |
| Weight (empty) kg | 61 |
| Weight (full) kg | 258 |
| Max. Operating Pressure (bar) | 5 |
| Test Pressure (bar) | 10 |
| Max. Working Temperature (c) | 95 |
| Heating Elements | 1 No. Incoloy Immersion |
| Unvented Kit Components | Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish |
| Heat Loss (W) | 83 |
| Heat up Time (mins) | 21 |
| Solar Coil Surface Area (m ²) | 0.58 |
| Solar Coil Rating (kW) | 16 |
| High Gain Coil Surface Area (m ²) | 2.8 |
| Product Code | TCIMVG-0200NFC |
| Energy Efficiency Class | C |

Dimensions

| | |
|---|------|
| A | 1490 |
| B | 540 |
| C | 196 |
| D | 246 |
| E | 386 |
| F | 486 |
| G | 536 |
| H | 586 |
| I | 791 |
| J | 981 |
| K | 1136 |
| L | 1211 |

