

Stainless Steel Buffer Tanks



Capacity	100L	125L	150L	170L	200L	250L	300L	400L	500L	600L
Code Without Coil	BBSSD-00100NFC	BBSSD-00125NFC	BBSSD-00150NFC	BBSSD-00170NFC	BBSSD-00200NFC	BBSSD-00250NFC	BBSSD-00300NFC	BBSSD-00400NFC	BBSSD-00500NFC	BBSSD-00600NFC
Code With Coil	-	-	BBSSI-00150NFC	BBSSI-00170NFC	BBSSI-00200NFC	BBSSI-00250NFC	BBSSI-00300NFC	BBSSI-00400NFC	BBSSI-00500NFC	BBSSI-00600NFC
Height (mm)	950	1030	1190	1310	1490	1815	1600	1570	1900	2200
Diameter (mm)	500	540	540	540	540	540	600	710	710	710
Weight Empty (kg)	22	26	30	32	34	43	47	62	75	90
Weight Full (kg)	122	151	180	202	234	293	347	462	575	690
No. Direct Connections	7	7	7	7	9	9	9	9	9	9
Diameter of Direct Connections	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"
Drain Off	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Standard Standing Loss (kWh/Day)	1.11	1.23	1.41	1.53	1.8	2.15	2.28	2.41	2.54	2.71
Eco80 Standing Loss (kWh/Day)	1.01	1.16	1.36	1.44	1.69	1.91	2.15	2.25	2.38	2.59