



Product Specification

Domestic Range

D

170 L Direct

Capacity	Type	Model	Installation
170L	Unvented	Direct	Floor Standing

Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 58 W

Constructive Specifications

Capacity	170 L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	33
Weight (full) kg	203
Max. Operating Pressure (bar)	5
Test Pressure (bar)	10
Max. Working Temperature (c)	95
Heating Elements	2 Incoloy Immersions
Unvented Kit Components	Expansion Vessel, Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Heat Loss (W)	58
Heat up Time (mins)	91
Energy Efficiency (%)	36
Annual EI. Consumption (kWh)	2830
Product Code	TCEMVD-0170LFD
Energy Efficiency Class	D

Dimensions

A	1270
B	540
C	196
D	211
E	631
F	881
G	1031

