

Inva Screed

Descriptive Specification

- The Inva Screed system is an overlay system
- The Inva Screed is to have a depth of 15mm
- The Inva Screed incorporates 12mm Pert pipe
- UFH Pipe laid in pre-grooved panels between structural floor and floor covering

Constructive Specifications

Dimensions	0.6m x 0.6m x 0.015m
Area	0.36m ²
Weight	kg/m ²
Pipe Diameter	12mm
Maximum Circuit Length	75m
Pipe Material	Pert
Floor Build-Up	15-33mm
Pipe Centres	100/150/200mm
Drying Times	8hr Foot Traffic / 72hr Floor Covering
Product Code (Inva Screed)	UZ-PANEL0000.6
Product Code (Self Leveling Compound 25kg)	UZ-LPC-SLC0025
Product Code (Perimeter Strip 50m)	UZ-LPC-PS00050

Heat Output

MWT	Tile	Wood Floor (TOG1)	6m Ply, U'lay & Carpet (TOG1.5)
30°C	56.6 W/m ²	40.2 W/m ²	30 W/m ²
35°C	84.9 W/m ²	60.32 W/m ²	45 W/m ²
40°C	113.2 W/m ²	80.43 W/m ²	60 W/m ²
45°C	141.5 W/m ²	100.53 W/m ²	75 W/m ²

