

Product Specification

Rapid System Horizontal

Descriptive Specification

- Just 12 components, including 4 moving parts, means less maintenance, lower service costs and greater reliability
- Flow rates up to 13.2 litres per minute at 35°C rise
- Saves money on energy bills as it condenses 100% of the time in both



	Rapid System 15	Rapid System 18	Rapid System 25	Rapid System 32
SIGNATURE OUTPUT	15	18	25	32
Type	Rapid			
Model	Horizontal			
Dimensions H X W X D	810 x 450 x 310			
Safety class	44			
NoX class	5			
NoX level	< 60			
Central Heating				
Nom. input rating (lower value)	15	18.7	25.7	32.7
Rated power	14.7	18.3	25.1	31.9
Max. CH water pressure	2.5			
Max. CH water temperature	90			
SEDBUK rating	A			
Harp efficiency	90.4	90.3	90.3	90.2
Flues				
Max horizontal	10			
Max vertical	10			
Standard flue dia	60/100	60/100	60/100	60/100
Installation				
Mains cold water inlet	-	-	-	-
Domestic hot water outlet	-	-	-	-
Gas connection	22			
Pressure relief valve	15			
Heating flow and return connections	22			
Condensate drain (flexible)	25			
Solar compatible	-	-	-	-
Product Fiche Intergas Rapid				
Seasonal space heating en. eff. class	A			
Heat rated outp. (power) (Prated)	15	18	25	25
Seasonal space heating en. eff. (η _s)	94	93	93	93
Annual energy consumption (QHE)			75	96
Sound power level (LWA)	50	50	50	50